



Meltblown, Sonic Bonded pads in Oil only

2MBWPB



Meltblown | Oil only | Pads | Sonic Bonded

Basis weight: 240 gsm*

Absorbency: 68 Litres | 18 US Gallons of oil**



Base Fibre: Polypropylene

Meltblown

| Product Code | Colour | Weight | Format | Size cm(inches) | Recycled Content | Units/Case | Weight/Case*** | LTL/Pallet | FTL/Pallet |
|--------------|--------|---------|--------|---------------------------|------------------|------------|------------------|------------|------------|
| Oil only | | | | | | | | | |
| 2MBWPB | White | 240 gsm | Pads | 38 cm x 46 cm (15" x 18") | 0%* | 100 | 4.1 kg (9.2 lbs) | 36 | 42 |

Sonic Bonded meltblown

Single Layer of meltblown polypropylene fibres with bond points



This product is in an Oil only format



This is one of our medium weight products



Pad size is 38 cm x 46 cm (15" x 18")



We recommend this product for removing oil on land

At 240 gsm these pads are an economical alternative to the bigger and heavier weight 286 gsm sorbent. There are 100 pads in a bale with each pad measuring 38 cm by 46 cm. The pads are made from a single layer of meltblown which is sonically bonded together. The sonic bonding points makes the pad less prone to stray fibres becoming detached. This gives the pad a very even structure which also contributes to the pad's good absorbency rate. These attributes help make the pad an industry standard construction because it offers all-round average performance but excellent versatility.

The pads are supplied in a clear plastic bag.

Key features

- The pad is made from a single layer of meltblown that is sonically bonded together.
- Good value and reliable performance.
- Made from high quality polypropylene.

Application

An economical choice for everyday Oil only situations. An excellent go-to-product for lighter duty outdoor Oil only tasks. Because the pads are Oil only, use mostly, but not exclusively outdoors.

Notes

- Fire retardant as per ASTM 726.
- Ensure that disposal of these sorbents complies with all relevant national regulations and guidelines.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

| Related Regulations | Description |
|---------------------------|---|
| 29CFR 1910.22(a)(2) | "The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition." |
| 29CFR 1910.120(j)(1)(vii) | "... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur." |