



SPECIFICATIONS

Product Description: **EXTENSION CORD**
 Part Number: **9540-50**
 Style: **STANDARD**

GENERAL DESCRIPTION:

This extra heavy duty cord powers 15 AMP, 125V. Weather resistant from -40° F to 167° F (-40° C to 75° C) with rugged and durable clear molded plugs. Outer jacket is flame, water and oil resistant. This cord meets OSHA specifications and is UL listed.

TECHNICAL SPECS:

Cord: 50' (15.24 m), 12/3 AWG, 15A
 Plug: NEMA 5-15P
 Connector: NEMA 5-15R
 Temp.: -40° F to 167° F (-40° C to 75° C)
 Weight: 5.9 lbs. (2.68 kg)
 Color: Yellow/Black Stripe



Product Description: **EXTENSION CORD**
 Part Number: **9540-50EX, 9540-60EX (220V)**
 Style: **EXPLOSION-PROOF**

GENERAL DESCRIPTION:

The 50' extension cord comes with a 20 AMP connector and plug. The weather resistant cord has a temperature range of -40° F to 221° F (-40° C to 105° C), is flexible and provides excellent abrasion resistance. Both the plug and receptacle have CSA Certifications for: Class I Division 1 & 2 Groups B, C, and D; Class II, Division 1 & 2 Groups F* and G.

TECHNICAL SPECS:

Cord: 50' (15.24 m), 10/3 AWG, 30A
 Plug: NEMA 20A, 1 HP, Explosion-Proof
 Connector: 125VAC, 20A w/ spring cover (PN 9540-50EX)
 220VAC, 20A w/ spring cover (PN 9540-60EX)
 Temp.: -40° F to 221° F (-40° C to 105° C)
 Weight: 15.5 lbs. (7.03 kg)
 Color: Black



HAZARDOUS LOCATION RATING:

Class: I	Class: II
Division 1 & 2	Division 1 & 2
Groups B, C and D	Groups F* and G

*Do not use where electrically conductive dusts are present (most coal dust is not electrically conductive)