



208 Litre (55 Gallon) Static Locking Lid Maintenance Spill Kit

SK-U55

Spill kit | 208 Litre | Maintenance | Static Overpack

Absorbency: 208 Litres | 55 US Gallons**

Base Fibre: Cellulose



| Product Code | Colour | Format | Size cm(inches) | Recycled Content | Units/Case | Weight/Case | LTL/Pallet | FTL/Pallet |
|--------------|--------|-----------|-----------------|------------------|------------|------------------|------------|------------|
| SK-U55 | Grey | Spill Kit | N/A | 60%* | 1 | 20.4 kg (45 lbs) | 4 | 4 |

208 Litre (55 US Gallon) Yellow drum with locking lid


The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A detachable lid with a locking rim keeps the contents secure before and after use.

This spill kits feature a combination of pads, socks and pillows that will contain and recover a 208 litre spill of oil-based or water-based fluid as well as equipment needed to handle the clean up process.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

Spill kit's contents include:



100 x Pads
size 40 cm x 46 cm (16" x 18")

The pads in this spill kit are medium weight Coldform2™ and feature recycled and renewable sourced natural fibres. A spun-bond lamination is added for extra strength. These pads will recover both oil and water-based fluids.



14 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. This tube is then filled with a next generation super absorbent flake core and sealed with a durable metal clip.



4 x Pillows
size 23 cm x 38 cm (9" x 15")

These pillows feature a spun-bond outer casing and a super absorbent flake core. The core is a next generation absorbent that will absorb and retain both oil-based and water-based fluids.



5 x Waste Bags

These are made from a tough grade of polythene. A cable tie is also supplied so that the waste can be secured safely.

2 pairs of gloves

Nitril gloves help to ensure safe handling of spilled substance.

2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.

1 neoprene drain cover

A 91 cm x 91 cm (36" x 36") cover that prevents spills from entering the drainage system.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

| Related Regulations | Description |
|----------------------------|---|
| 29 CFR 1910.120(j)(1)(vii) | ...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.120(j)(1)(vii) | U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.22(a)(2) | The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. |
| 40 CFR 263.31 | Transporters "must clean up any hazardous waste discharge that occurs during transportation. |