Data sheet - Spill Kits



208 Litre (55 Gallon) Static Locking Lid Oil only Spill Kit

SK-055

Spill kit | 208 Litre | Oil only | Static Overpack

Absorbency: 208 Litres | 55 US Gallons of oil*


Base Fibre: Cellulose and polypropylene

Product Code	Colour	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
SK-055	White	Spill Kit	N/A	60%*	1	20.4 kg (45 lbs)	4	4

208 Litre (55 US Gallon) Yellow drum with locking lid

The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A detachable lid with a locking rim keeps the contents secure before and after use.

Spill kit's contents include:



size 40 cm x 46 cm (16" x 18")

These Oil only pads are very absorbent 240 gsm weight Coldform2™ made from recycled and renewable sourced natural fibres. They have a spun-bond lamination added for extra strength.

2 pairs of gloves

Nitryl gloves help to ensure safe handling of spilled substance.



14 x Socks size 8 cm x 1.2 m (3" x 4')

Oil only socks are made with a strong spun-bond outer sleeve and a recycled meltblown polypropylene and cellulose core, producing a resilient nolint product.

2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.

This spill kits feature a combination of pads, socks and pillows that will contain and recover a 208 litre spill as well as the essential equipment needed to handle the clean up process.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.



4 x Pillows size 23 cm x 38 cm (9" x 15")

These Oil only pillows are made from a spun-bond outer casing that is both stitched and heat sealed to enclose a recycled polypropylene core. The surface is fast-wicking so promotes faster absorption.



5 x Waste Bags

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

1 neoprene drain cover

A 91 cm x 91 cm (36" x 36") cover that prevents spills from entering the drainage system.

- Basis weights and recycled content are ± 5%
- ** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.
- *** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations Description

29 CFR 1910.120(j)(1)(vii) 29 CFR 1910.120(j)(1)(vii)

29 CFR 1910.22(a)(2) 40 CFR 263.31 ...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Transporters "must clean up any hazardous waste discharge that occurs during transportation.